MAGNETO-MECHANICS OF MAGNETIC SHAPE-MEMORY CRYSTALS WITH MICROPEENED SURFACES



ZANE HARBISON, GIANELLA CONDOR, AMMON BUTLER, JOHN MARTIN, SHANE PALMER, PAUL LINDQUIST, PETER MULLNER

Putting a magnetically-powered "car" in your body.


INTRODUCTION

- Magnetic Shape-Memory (MSM) Materials
- Nickel-Manganese-Gallium (Ni₂MnGa)
- Twinning Deformation Mechanism

MSMs & ACTUATION

Movement Driven Purely by Magnets

- A. Twin Boundaries
- B. Pumps, Positioning Devices, and Circuit Breakers




PROCEDURE


- 1. Growing the Crystal
- 4. Micropeening
- 2. Cutting

3. Polishing


- 5. Micromechanical Testing
- 6.
- 6. Magnetic Reset

Micropeening






Micromechanical Testing



DATA: STRESS & STRAIN


- 3 MPa Limit
- Increasing StressThresholds
- Decrease in Strain



CONCLUSIONS

- Twin Boundary Character
- Appear at Stress Peaks
- Singular vs. Numerous
- Quantitative Relationship: Micropeening & Stress


Twin Boundary Movement



FUTURE PLANS

25 psi — A Happy Medium?

- More Systematic Experimentation
 - Micropeen at lower pressures



Twinning Comparison:
Polished (top),
Micropeened (bottom)